

Daily use




How to create Secondary container labels for hazardous chemicals

A secondary label is used on smaller containers, such as spray bottles, jugs, or jars that chemicals are transferred to from the primary container once within the workplace. It contains information about the products, such as its ingredients and nutritional values, health and safety warnings, instructions for use, manufacturer/supplier and contact information, or detailed tracking and product information in a barcode format.

According to OSHA, secondary containers need to comply with the labeling requirements.

On the label icon, you can generate Secondary Container labels, you can also edit the information shown on the Label and add your own information notes to the labels.

Click here to [open SDS Manager to create Secondary container labels \(require login\)](#)

Product Name ↑	Supplier Name	Location	Signal word	Pictograms & Controls	Substance hazard H S E	Actions
1,2-Dichlorobenzene	AccuStandard, Inc	Hazardous Area	Warning			

The label has respective QR codes to view the actual SDS file and track chemical usage and disposal.

Icons from the SDS, Hazard statements and Prevention statements are also shown in the label.

Daily use

A4 (8.5"x11")

A4 (8.5"x11")

A5 (5.5"x8.5")

A6 (4"x6")

A7 (3"x4")

2"x4"



A8 (2"x3")

A9 (1.5"x2")

1"x2"


A10 (1"x1.5")


Use standard statement description

1 / 1 | - 67% + |  

3-D Laserscanning Cleaner
Spray

Company Name: Helling GmbH
Signal Word: Danger


View PDF




Track Usage








Hazard Statements

H222: Extremely flammable aerosol;
H229: Pressurized container: may burst if heated;
H319: Causes serious eye irritation;
H336: May cause drowsiness or dizziness

Precautionary Statements

P102: Keep out of reach of children.;
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking;
P211: Do not spray on an open flame or other ignition source.;
P251: Do not pierce or burn, even after use.;
P271: Use only outdoors or in a well-ventilated area.;
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.;
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.





Ingredients:

EC/CAS	Chemical Name	Concentration
200-661-7/67-63-0	Isopropanol	70 - 80 %
200-661-7/106-97-8	Butane	15 - 20 %
203-448-7/74-98-6	Propane	6 - 10 %

Supplier Name: Helling GmbH

Emergency Contact: Poison Control Center
Emergency Telephone: 800-222-1222


When smaller formats are chosen, less information is displayed on the label due to the size constraints. Below is an example of a 2" label that can be printed on a Dymo sticker printer.

Page 2 / 6

© 2025 SDS Manager <eb@aston.no> | 2025-07-07 08:56


URL: <https://sdsmanager.com/faq/content/37/243/en/how-to-create-secondary-container-labels-for-hazardous-chemicals/>

Daily use




SDS Manager fully supports all major Avery label formats. When printing to Avery labels, you can easily choose which specific label position on the sheet you'd like to use, ensuring efficient and flexible printing.

Daily use




You can add custom notes to the labels, and categorize them as **Info**, **Warning**, or **Danger**. Each note will be color-coded accordingly to reflect its severity.

Daily use



See the example below to preview how notes will appear on the labels, including their corresponding colors based on severity level.



Daily use

By using the **"Hazard Statements from PDF"** option, the exact text from Section 2 of the Safety Data Sheet will be displayed on the label. You can also click the **edit pencil** icon to modify the text as needed.

Print format

A6 (4"x6")

Add PPE icons

NFPAHMIS

Hazard statements

Use standard statement descriptionFrom Pdf

Edit information message

1 / 1175%

1

AATREX LIQUID 480
Company Name: Syngenta Canada Inc
Signal Word: Warning

Instruction

View PDF

⚠️ Use only in ventilated areas

Hazard Statements

H373 May cause damage to organs (Kidney) through prolonged or repeated exposure.
H373 May cause damage to organs (Heart) through prolonged or repeated exposure if swallowed.

Precautionary Statements

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.P314 Get medical advice/ attention if you feel unwell.P501 Dispose of contents/ containe posal plant.

Chemical Name

Concentration

Atrazine>43.5
Ethylene glycol>=>5-<10
Alcohols, C₁₁₋₁₄-isooalcohols, C₁₃-rich, ethoxylated>>=1-<5

Supplier Name:

Syngenta Canada Inc

Emergency Contact:

Poison Control Center

Emergency Telephone:

800-222-1222

Unique solution ID: #1051

Author: n/a

Last update: 2025-06-12 16:03