

# Daily use

## How to create Secondary container labels for hazardous chemicals

A secondary label is used on smaller containers, such as spray bottles, jugs, or jars that chemicals are transferred to from the primary container once within the workplace. It contains information about the products, such as its ingredients and nutritional values, health and safety warnings, instructions for use, manufacturer/supplier and contact information, or detailed tracking and product information in a barcode format.

According to OSHA, secondary containers need to comply with the labeling requirements.

On the label icon, you can generate Secondary Container labels.

Click here to [open SDS Manager to create Secondary container labels \(require login\)](#)

Product Name ↑	Supplier Name	Location	Signal word	Pictograms & Controls	Substance hazard			Actions
					H	S	E	
1,2-Dichlorobenzene	AccuStandard, Inc	Hazardous Area	Warning					

The label has respective QR codes to view the actual SDS file and track chemical usage and disposal.

Icons from the SDS, Hazard statements and Prevention statements are also shown in the label.

# Daily use

A4 (8.5"x11")

A4 (8.5"x11")

A5 (5.5"x8.5")

A6 (4"x6")

A7 (3"x4")

2"x4"

A8 (2"x3")

A9 (1.5"x2")

1"x2"


A10 (1"x1.5")


Use standard statement description

1 / 1 | - 67% + | [ ] [ ]

3-D Laserscanning Cleaner  
Spray

Company Name: Helling GmbH  
Signal Word: Danger

  
View PDF


  
Track Usage

**Hazard Statements**

H222: Extremely flammable aerosol;  
H229: Pressurized container: may burst if heated;  
H319: Causes serious eye irritation;  
H336: May cause drowsiness or dizziness

**Precautionary Statements**

P102: Keep out of reach of children.;  
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking;  
P211: Do not spray on an open flame or other ignition source.;  
P251: Do not pierce or burn, even after use.;  
P271: Use only outdoors or in a well-ventilated area.;  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.;  
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.



**Ingredients:**


EC/CAS	Chemical Name	Concentration
200-661-7/67-63-0	Isopropanol	70 - 80 %
200-661-7/106-97-8	Butane	15 - 20 %
203-448-7/74-98-6	Propane	6 - 10 %

**Supplier Name:** Helling GmbH

Emergency Contact: Poison Control Center  
Emergency Telephone: 800-222-1222


When smaller formats are chosen, less information is displayed on the label due to the size constraints. Below is an example of a 2" label that can be printed on a Dymo sticker printer.

# Daily use



SDS Manager fully supports all major Avery label formats. When printing to Avery labels, you can easily choose which specific label position on the sheet you'd like to use, ensuring efficient and flexible printing.

## Daily use



Unique solution ID: #1051

Author: n/a

Last update: 2024-10-24 15:53